

PET CF

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
SDS ID: UM00013
Issue date: 12/6/2023 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : PET CF
(Blue, Black, Gray)

1.2. Recommended use and restrictions on use

Use of the substance/mixture : 3D-Printer filament
Restrictions on use : This product must not be used in applications other than those identified above, without first seeking advice of the supplier

1.3. Supplier

US Responsible Party	Supplier
MakerBot Industries, LLC c/o UltiMaker 55 Water St, Fl 51, New York, NY 10041 Tel +1 347 334 6800 product-compliance@ultimaker.com	UltiMaker Watermolenweg 2 Geldermalsen, 4191 PN - The Netherlands T +31 (0) 88 383 4000 (9 AM - 5 PM CET) product-compliance@Ultimaker.com

1.4. Emergency telephone number

Emergency number : +1 347 334 6800

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Not classified

2.2. GHS Label elements, including precautionary statements

Product is non-hazardous because all hazardous ingredients are encapsulated within a polymer. No labeling obligation.

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : Risk of thermal burns on contact with molten product.

2.4. Unknown acute toxicity (GHS US)

Not applicable

PET CF

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Comments : Proprietary Formulation

Name	Product identifier	Conc. (% w/w)
Pyromellitic dianhydride	CAS-No.: 89-32-7	< 1
Reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight \leq 700)	CAS-No.: 25068-38-6	< 0.25
Carbon black (Additive for PET CF Black)	CAS-No.: 1333-86-4	

Comments : Pyromellitic dianhydride (CAS# 89-32-7) and Reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight \leq 700) (CAS# 25068-38-6) were not detected in emission tests conducted during printing while following the measuring method of UL-2904. Because the maximum concentration in the product (filament) is very low and it is not detected during emission tests, the risk of significant exposure to this substance, both during printing and during handling of the filament and printed parts (both considered articles) is considered negligible.

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. In molten state: Hazardous vapors may be released.
First-aid measures after skin contact : In case of contact with molten product, cool rapidly with water and seek immediate medical attention. Do not attempt to remove molten product from skin because skin will tear easily. Burns caused by molten material must be treated clinically. Wash skin with plenty of water and soap. Take off contaminated clothing.
First-aid measures after ingestion : If you feel unwell, seek medical advice.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : No acute and delayed symptoms and effects are observed.
Symptoms/effects after skin contact : Risk of thermal burns on contact with molten product.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

PET CF

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

5.2. Specific hazards arising from the chemical

Explosion hazard : Material can accumulate some static charge during transfer. Prevent build-up of electrostatic charges (e.g, by grounding).

Hazardous decomposition products in case of fire : Under fire conditions, hazardous fumes will be present: Carbon dioxide, Carbon monoxide, Acids, Aldehydes, Ammonia, Hydrogen cyanide, nitrile, nitrogen oxides (NOx) and sulphur oxides.

5.3. Special protective equipment and precautions for fire-fighters

Precautionary measures fire : Do not allow run-off from fire-fighting to enter drains or water courses.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : During mechanical post processing of 3D printed parts avoid exposure to dust and apply external air extraction to outside air or a suitable filter.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment. Refer to section 8.2. Remove contaminated clothing and shoes.

Emergency procedures : None in particular. Do not breathe dust. In molten state: Do not breathe vapors. Ventilate spillage area. Avoid contact with skin, eyes and clothing. Evacuate unnecessary personnel.

Measures in case of dust release : Caution : this product can cause the floor to be very slippery.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Sweep up and put in a closed container for disposal. If melted: allow liquid to solidify before taking it up.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of residues refer to section 13: Disposal considerations " " .

PET CF

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : During mechanical post processing of 3D printed parts avoid exposure to dust and apply external air extraction to outside air or a suitable filter. Avoid dust formation. Do not breathe dust. In molten state: Do not breathe vapors. Avoid contact with skin, eyes and clothing. Wear personal protective equipment.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : To guarantee the quality and properties of the product: Store in a well-ventilated place. Store in original container. Keep container tightly closed to avoid moisture absorption and contamination. Prevent moisture contact.
- Heat-ignition : Keep away from heat, sparks and flames. Keep out of direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

PET CF (Blue, Black, Gray)	
No additional information available	
Carbon black (Additive for PET CF Black) (1333-86-4)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Carbon black
ACGIH TWA (mg/m ³)	3 mg/m ³ (I - Inhalable particulate matter)
Remark (ACGIH)	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2023
USA - OSHA - Occupational Exposure Limits	
Local name	Carbon black
OSHA PEL (TWA) (mg/m ³)	3.5 mg/m ³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)	
No additional information available	

PET CF

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Pyromellitic dianhydride (89-32-7)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Use process enclosures, local exhaust ventilation or other engineering controls to keep airborne levels below specified exposure limits. If user operations generate dust, fumes or mist, use ventilation to keep exposure to airborne particles below the exposure limit. During mechanical post processing of 3D printed parts avoid exposure to dust and apply external air extraction to outside air or a suitable filter. Ventilation conditions (1 printer): Provide a good standard of general ventilation, not less than 2 air changes per hour (assumes a room volume of: 30 m³).

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

None under normal conditions. Use insulated gloves when handling this material hot

Type	Material	Permeation	Thickness (mm)	Penetration
In molten state: Chemically resistant protective gloves, Heat-resistant	Nitrile rubber (NBR)	6 (> 480 minutes)	>0.35	

Eye protection:

None under normal use. In molten state: Wear eye protection

Type	Use	Characteristics
Safety glasses with side shields	In molten state	

Skin and body protection:

None under normal use. In molten state: Wear suitable protective clothing

Type
Long sleeved protective clothing

Respiratory protection:

None under normal use. In molten state: In case of insufficient ventilation, wear suitable respiratory equipment

Device	Filter type	Condition
Air-Purifying Respirator (APR), disposable	Type B/P2	

Thermal hazard protection:

Risk of thermal burns on contact with molten product. Hazardous vapors may be released. In molten state: Use respiratory protection/heat resistant gloves.

PET CF

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Wash hands immediately after handling the product. Take off contaminated clothing and wash before reuse.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Filament.
Color	: Various colours Black Blue or Gray
Odor	: odorless
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: Not applicable
Boiling point	: No data available
Flash point	: Not applicable
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Density	: 1.4 g/cm ³
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: No data available
Explosion limits	: Not applicable
Explosive properties	: Dust can form an explosive mixture with air.
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

No additional information available

PET CF

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under fire conditions, hazardous fumes will be present: Carbon dioxide, Carbon monoxide, Acids, Aldehydes, Ammonia, Hydrogen cyanide, nitrile, nitrogen oxides (NOx) and sulphur oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

Reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight \leq 700) (25068-38-6)

LD50 oral rat	> 2000 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
---------------	---

LD50 dermal rat	> 2000 mg/kg OECD 402
-----------------	-----------------------

Pyromellitic dianhydride (89-32-7)

LD50 oral rat	> 2000 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method), Guideline: EU Method B.1 bis (Acute Oral Toxicity - Fixed Dose Procedure)
---------------	--

LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
-----------------	---

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : Not classified. Product is non-hazardous because all hazardous ingredients are encapsulated within a polymer

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Carbon black (Additive for PET CF Black) (1333-86-4)

IARC group	2B - Possibly carcinogenic to humans, only for airborne, unbound particles of respirable size
------------	---

Reproductive toxicity : Not classified

PET CF

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Pyromellitic dianhydride (89-32-7)	
Additional information	Based on available data, the classification criteria are not met,(OECD 421 method)
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: Not applicable
Symptoms/effects	: No acute and delayed symptoms and effects are observed.
Symptoms/effects after skin contact	: Risk of thermal burns on contact with molten product.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight \leq 700) (25068-38-6)	
LC50 fish 1	1.5 ml/l OECD 203
EC50 Daphnia 1	1.7 mg/l
NOEC chronic crustacea	0.3 mg/l OECD 211

Pyromellitic dianhydride (89-32-7)	
LC50 fish 1	> 100 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 Daphnia 1	63 mg/l Test organisms (species): Daphnia magna
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

PET CF (Blue, Black, Gray)	
Persistence and degradability	No additional information available.

Reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight \leq 700) (25068-38-6)	
Persistence and degradability	Not rapidly degradable.

Pyromellitic dianhydride (89-32-7)	
Persistence and degradability	Readily biodegradable.
Biodegradation	100 %

PET CF

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential

PET CF (Blue, Black, Gray)

Bioaccumulative potential	No additional information available.
---------------------------	--------------------------------------

Reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight \leq 700) (25068-38-6)

Bioconcentration factor (BCF REACH)	31
-------------------------------------	----

Partition coefficient n-octanol/water (Log Pow)	3.242 OECD 117
---	----------------

Pyromellitic dianhydride (89-32-7)

Partition coefficient n-octanol/water (Log Pow)	\leq -2.03
---	--------------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation : Dispose of in accordance with relevant local regulations.
Product/Packaging disposal recommendations : Empty containers should be taken for recycling, recovery or waste in accordance with local regulation.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
Not regulated for transport			
14.2. Proper Shipping Name			
Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)			
Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Not applicable	Not applicable	Not applicable	Not applicable

PET CF

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT	TDG	IMDG	IATA
No supplementary information available			

14.6. Special precautions for user

DOT

No data available

TDG

No data available

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

Carbon black (Additive for PET CF Black) (1333-86-4)

Listed on IARC (International Agency for Research on Cancer)

PET CF

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations

PET CF (Blue, Black, Gray)

U.S. - California - Proposition 65 - Other information	For product containing Carbon Black: California Proposition 65 lists Carbon Black (airborne, unbound particles of respirable size) as a substance known to the State of California to cause cancer. Some UltiMaker filaments contain low concentrations of Carbon Black, which is homogeneously bound in the polymer matrix. Given the Carbon Black is bound and concentrations are low, the risk of exposure to 'airborne, unbound particles of respirable size' during printing is considered negligible. In case 3D-prints undergo post-processing that causes dust formation, UltiMaker recommends to re-assess whether those activities may lead to significant exposure under those particular conditions and apply appropriate measures when necessary. Appropriate measures in such cases may include additional ventilation, air extraction or (face) masks, depending on the level of potential exposure.
--	--

Carbon black (Additive for PET CF Black) (1333-86-4)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

SECTION 16: Other information

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Abbreviations and acronyms	
CAS	Chemical Abstract Service number
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
TDG	Transportation of Dangerous Goods
CAS-No.	Chemical Abstract Service number
DOT	Department of Transport
ED	Endocrine disrupting properties
EN	European Standard
GHS	Globally Harmonized System of Classification and Labelling of Chemicals
IARC	International Agency for Research on Cancer

Indication of changes:

Not applicable.

SDS US (GHS HazCom 2012) - RHDHV

PET CF

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.